



**SECTION THRU
SHELF & BRACKET**

BRACKET DETAIL

- A.** TWO 14 GA. (1.8MM) S/S BRACKETS TO BE SUPPLIED ON SHELVES UP TO 6'-0" (1800MM) IN LENGTH. SHELVES LONGER THAN 6'-0" (1800MM) TO HAVE ADDITIONAL SUPPORTS EQUALLY SPACED. MAXIMUM OF 5'-0" (1525MM) BETWEEN BRACKET EACH BRACKET DRILLED AND SECURED TO WALL WITH A MINIMUM OF TWO 1/4" (5MM) X 20 S/S ROUNDHEAD BOLTS AND S/S LOCKWASHERS ANCHORED WITH TOGGLES OR LEAD EXPANSION SHIELDS. VERIFY WALL CONSTRUCTION AND PROVIDE BACKING IF REQUIRED. SEE DTL. 7.05.
- B.** SHELF 16 GA. (1.5MM) S/S CONSTRUCTION WITH ALL JOINTS WELDED, GROUND SMOOTH AND POLISHED. SHELVES TO HAVE STUDS WELDED TO UNDERSIDE. DRILL BRACKET, FASTEN WITH S/S LOCKWASHERS AND S/S CAP NUTS.
- C.** 2" (50MM) CLEAR REAR AND ENDS.
- D.** FULLY WELD, GRIND SMOOTH AND POLISH.
- E.** COVED BEND ACCEPTABLE, BUT NOT REQUIRED.
- W.** WIDTH, AS SPECIFIED.

APPROVED: 08-01-01