Make every pull fast and easy

Yellow 77®
Wax-based wire lubricant – the industry standard.

ClearGlide™
Clear, polymer-based wire lubricant for easy clean-up.

Wire Pulling Lubricant Selection Guide

	Yellow 77® Plus Wire Pulling Lubricant	Yellow 77® Wire Pulling Lubricant	ClearGlide™ Wire Pulling Lubricant	Aqua-Gel® II Cable Pulling Lubricant	Aqua-Gel® IIP Cable Pulling Lubricant	Aqua-Gel® CW Cable Pulling Lubricant
Application	High Temperature – Construction & Maintenance	General Purpose – Construction & Maintenance	Utility – Construction, Maintenance & Telecommunications	Utility – Construction & Maintenance	Utility – Construction & Maintenance	Cold Weather – Construction & Maintenance
Base	Wax	Wax	Polymer	Polymer	Polymer	Polymer
Average Coefficient of Friction	0.034	0.07	0.032	0.052	0.050	0.055
Temperature Range	30°F – 190°F (-1°C – 88°C)	32°F – 130°F (0°C – 54°C)	30°F – 180°F (-1°C – 82°C)	28°F – 180°F (-2°C – 82°C)	28°F – 180°F (-2°C – 82°C)	-25°F – 180°F (-32°C – 82°C)
COMPATIBILITY (Cable Types):						
Rubber	•	•	•	•	•	•
Neoprene	•	•	•	•	•	•
Nylon	•	•	•	•	•	•
PVC	•	•	•	•	•	•
High-density or cross-linked polyethylene	•	•	•	•	•	•
Low-density polyethylene	•		•	•	•	•
Semiconducting jacket	•		•	•	•	•
Hypalon	•	•	•	•	•	•