

Yellow 77® Plus Wire Pulling Lubricant

- DuPont™ TEFLON® additive provides greater lubricity than other wax-based lubricants
- Safe to use with all cable types
- Remains stable in high temperatures – usable from 30°F to 190°F (-1°C to 88°C)
- Dries slowly to a thin, non-conducting film that won't harden in conduit
- Clings to cable throughout long runs
- Easy to apply by hand or with pump
- Creamy texture applies easily and uniformly
- Homogeneous blend requires no mixing
- Won't dry out – surface coat forms to control evaporation
- Environmentally safe – non-toxic, non-flammable and non-corrosive

Description	Cat. No.
1-qt. Squeeze bottle	31-398
1-gal. Bucket	31-391
5-gal. Bucket	31-395

DuPont™ and TEFLON® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



Yellow 77® Wire Pulling Lubricant

- Wax-based formula provides superior lubricity
- Safe to use with most cable types except low-density polyethylene and semi-conducting jackets
- Won't breakdown or separate after repeated exposure to freezing temperatures
- Dries to a thin, non-conductive film that won't clog conduit
- Clings to cable throughout long pulls
- Easy to apply by hand or with pump
- Creamy texture applies easily and uniformly
- Homogeneous blend requires no mixing
- Won't dry out – surface coat forms to control evaporation
- Environmentally safe – non-toxic, non-flammable and non-corrosive

Description	Cat. No.
15-oz. Aerosol	31-356
1-qt. Squeeze bottle	31-358
1-qt. Tub	31-350
1-gal. Bucket	31-351
5-gal. Bucket	31-355
55-gal. Drum	31-365

