Cable Ties

All IDEAL cable ties feature:

- Unique triple-tooth design to lock ties securely and permanently into place
- Bent starter tip for quick and easy installation (except ladder cable ties)
- 100% virgin nylon construction – Type 6/6
- Self-extinguishing characteristics – UL flame resistant, Class: V-2
- Natural and black weather resistant ties rated at -40°F to 185°F (-40°C to 85°C); black heat-stabilized ties rated at -40°F to 221°F (-40°C to 105°C)

Powr-Tie™ Premium Cable Ties

- Modular alignment during the manufacturing process for greater tensile strength and greater resistance to environmental extremes
- Higher petrochemical resistance than other nylon ties
- Lightweight and compact – ideal for applications where strength, space and weight requirements must be optimized

Premium Cable Ties

7.5 in. Length, .190 in. width, bundle dia. 1/16 in. min. – 1-3/4 in. max.
Min. loop tensile strength: 50 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-1-9	100	**15-149**
Black heat-stabilized	MS-3367-1-0	100	**15-140**
Natural	MS-3367-1-9	1,000	**15-349**
Black heat-stabilized	MS-3367-1-0	1,000	**15-340**

15 in. Length, .190 in. width, bundle dia. 1/16 in. min. – 4 in. max.
Min. loop tensile strength: 50 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-2-9	100	**15-139**
Black heat-stabilized	MS-3367-2-0	100	**15-130**
Natural	MS-3367-2-9	500	**15-339**
Black heat-stabilized	MS-3367-2-0	500	**15-330**

Powr-Tie™ Cable Ties

Miniature Cable Ties

4 in. Length, .100 in. width, bundle dia. 1/16 in. min. – 7/8 in. max.
Min. loop tensile strength: 18 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-4-9	100	**15-609**
Black weather-resistant	MS-3367-4-0	100	**15-600**
Natural	MS-3367-4-9	1,000	**15-809**
Black weather-resistant	MS-3367-4-0	1,000	**15-800**

Intermediate Cable Ties

5.5 in. Length, .140 in. width, bundle dia. 1/16 in. min. – 1-1/4 in. max.
Min. loop tensile strength: 40 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-5-9	100	**15-629**
Black weather-resistant	MS-3367-5-0	100	**15-620**
Natural	MS-3367-5-9	1,000	**15-829**
Black weather-resistant	MS-3367-5-0	1,000	**15-820**

Standard Cable Ties

7.5 in. Length, .190 in. width, bundle dia. 1/16 in. min. – 1-3/4 in. max.
Min. loop tensile strength: 50 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-1-9	100	**15-649**
Black weather-resistant	MS-3367-1-0	100	**15-640**
Natural	MS-3367-1-9	1,000	**15-849**
Black weather-resistant	MS-3367-1-0	1,000	**15-840**

11 in. Length, .190 in. width, bundle dia. 1/16 in. min. – 3 in. max.
Min. loop tensile strength: 50 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-7-9	100	**15-639**
Black weather-resistant	MS-3367-7-0	100	**15-630**
Natural	MS-3367-7-9	1,000	**15-839**
Black weather-resistant	MS-3367-7-0	1,000	**15-830**

15 in. Length, .190 in. width, bundle dia. 1/16 in. min. – 4 in. max.
Min. loop tensile strength: 50 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-2-9	100	**15-659**
Black weather-resistant	MS-3367-2-0	100	**15-650**
Natural	MS-3367-2-9	500	**15-859**
Black weather-resistant	MS-3367-2-0	500	**15-850**