Powr-Tie™ Lashing Ties

- Greatest holding strength of all cable ties
- Withstand extreme temperatures and ultraviolet light

Heavy-Duty Lashing Ties

14.5 in. Length, .250 in. width, bundle dia. 3/16 in. min. – 4 in. max.
Min. loop tensile strength: 120 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-3-9	50	**15-669**
Black weather-resistant	MS-3367-3-0	50	**15-660**
Natural	MS-3367-3-9	100	**15-869**
Black weather-resistant	MS-3367-3-0	100	**15-860**

21 in. Length, .310 in. width, bundle dia. 3/16 in. min. – 6 in. max.
Min. loop tensile strength: 120 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-3-9	50	**15-679**
Black weather-resistant	MS-3367-3-0	50	**15-670**

28 in. Length, .310 in. width, bundle dia. 3/16 in. min. – 8 in. max.
Min. loop tensile strength: 120 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3367-6-9	50	**15-689**
Black weather-resistant	MS-3367-6-0	50	**15-680**

Extra Heavy-Duty Lashing Ties

33 in. Length, .310 in. width, bundle dia. 1/4 in. min. – 10 in. max.
Min. loop tensile strength: 175 lbs.

Description	Qty./Bag	Cat. No.
Black weather-resistant	25	**15-681**

Powr-Tie™ I.D. Marker Ties

- Built-in identification plate for permanent marking and identification of cables in intricate cable layouts

Miniature Identification Cable Ties

4 in. Length, .100 in. width, bundle dia. 3/16 in. min. – 7/8 in. max.
Min. loop tensile strength: 18 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3368-5-9E	100	**15-695**
Natural	MS-3368-5-9E	1,000	**15-895**

Standard Identification Cable Ties

7.5 in. Length, .190 in. width, bundle dia. 3/16 in. min. – 1-3/4 in. max.
Min. loop tensile strength: 50 lbs.

Description	MIL-SPEC	Qty./Bag	Cat. No.
Natural	MS-3368-1-9A	100	**15-696**
Natural	MS-3368-1-9A	1,000	**15-896**

Powr-Tie™ Screw Mount Cable Ties

- Flexible, built-in mounting head for mounting wires directly to chassis panels, walls or other surfaces
- Heavy-duty ties feature lashing tie strength for long-lasting cable mounting

Standard Screw Mount Ties

7.5 in. Length, .190 in. width, bundle dia. 1/16 in. min. – 1-3/4 in. max.
Min. loop tensile strength: 50 lbs.; #10 screw

Description	Qty./Bag	Cat. No.
Natural	100	**15-749**
Black weather-resistant	100	**15-740**
Natural	1,000	**15-949**
Black weather-resistant	1,000	**15-940**

Heavy-Duty Screw Mount Ties

14.5 in. Length, .250 in. width, bundle dia. 3/16 in. min. – 4 in. max.
Min. loop tensile strength: 120 lbs.; 1/4 in. screw

Description	Qty./Bag	Cat. No.
Natural	50	**15-769**
Black weather-resistant	50	**15-760**
Natural	100	**15-969**
Black weather-resistant	100	**15-960**

Powr-Tie™ Ladder Cable Ties



- Use for bundling and harnessing in lower strength applications
- Lightweight and flexible for difficult locations or tight places

Ladder Cable Ties

7 in. Length, .140 in. width, bundle dia. 1/16 in. min. – 1-3/4 in. max.
Min. loop tensile strength: 40 lbs.

Description	Qty./Bag	Cat. No.
Natural	100	**15-249**
Black heat-stabilized	100	**15-240**
Natural	1,000	**15-449**
Black heat-stabilized	1,000	**15-440**

11 in. Length, .140 in. width, bundle dia. 1/16 in. min. – 3 in. max.
Min. loop tensile strength: 40 lbs.

Description	Qty./Bag	Cat. No.
Natural	100	**15-239**
Black heat-stabilized	100	**15-230**
Natural	1,000	**15-439**
Black heat-stabilized	1,000	**15-430**