

## Thermo-Shrink® Heat Shrink Kit

Kit includes:

- Eleven sizes of thin-wall heat shrinkable tubing disks (3/64 in. – 1 in.)
- 101 Plus Heat Gun with three different nozzles for controlled temperature ranges – 600°F to 1,250°F (315°C to 675°C)
- Small deflector
- Premium T®-Cutter Wire Cutter



Description	Cat. No.
Kit includes: 45-223, 46-013, 46-923, 46-941, & 46-600 through 46-610	<b>46-007</b>

## High-Capacity Heat Guns



- Increased air volume for broad-range applications
- For all heat shrinkable tubing (including TEFLON®)
- Whisper-quiet brushless motor requires no maintenance
- Lightweight balanced design for hand-held or bench use
- Thermally insulated nozzles interchange quickly with color-coding to identify heat ranges – 700°F to 1,100°F (370°C to 595°C)
- Safety grounded, non-metallic housing
- Asbestos-free insulated construction
- Deflectors and adapters available for heat concentration and solder-sleeve applications

### Specifications

Dimensions	10-3/8 in. long (264mm) 9 in. high (229mm)
Weight	3-1/2 lbs. (1.6kg)
Input	120V 60 Hz., 12.5 amps 220V, 50 Hz., 6.0 amps
Motor	Shaded pole
Nozzle Length	4-3/8 in. (111mm)
Nozzle Opening	1-1/4 in. dia. (32mm)
Cord Length	7 ft. (2m)

Description	Cat. No.
High-Capacity Heat Gun w/gold nozzle 120V, 60 Hz., 12.5A, UL Listed	<b>46-021</b>
High-Capacity Heat Gun w/gold nozzle 220V, 50 Hz., 6.0A	<b>46-022</b>

## 101 Plus Heat Guns



- For applications with specific heat requirements or small target areas – perfect for electronic assembly
- Exclusive brushless motor minimizes both motor noise and maintenance
- Thermally insulated nozzles interchange quickly with color-coding to identify heat ranges – 600°F to 1,250°F (315°C to 675°C)
- Balanced design eliminates operator fatigue
- Impact-resistant housing stands up to rugged environments and the demands of industrial work

### Specifications

Dimensions	8-3/4 in. long, (222mm) 7-3/4 in. high (197mm)
Weight	2 lbs. (0.9kg)
Input	120V, 60 Hz., 4.5 amps 220V, 50/60 Hz., 2.0 amps
Motor	Shaded pole
Nozzle Length	3-7/8 in. (98.5mm)
Nozzle Opening	1 in. dia. (25.5mm)
Cord Length	7 ft. (2m)

Description	Cat. No.
101 Plus Heat Gun w/gold nozzle 120V, 60 Hz., 4.5A, UL Listed	<b>46-013</b>
101 Plus Heat Gun w/ESD case and gold nozzle 120V, 60 Hz., 4.5A, UL Listed	<b>46-113</b>
101 Plus Heat Gun w/gold nozzle 220V, 50/60 Hz., 2.0A	<b>46-014</b>
Heat Gun stand for 46-013 & 46-014	<b>46-105</b>