

200 Amp Clamp Meters

- 200A current capability
- Audible continuity
- Diode test
- Data hold/max hold
- Low battery indication
- Overload protection on all ranges
- Silicone leads
- Integral lead storage
- Audible dangerous voltage warning
- Sleep mode
- Ergonomic hourglass shape
- Compact clamp head
Includes carrying case



Clamp Meters

Description	Cat. No.
Clamp Meter w/vibration mode to verify AC voltage, harmonics indicator, non-contact voltage, capacitance, CAT III – 1000V rated	61-702
Clamp Meter w/non-contact voltage, capacitance, frequency, CAT III – 600V rated	61-701
Clamp Meter w/frequency, CAT III – 600V rated	61-700

Specifications	61-700		61-701		61-702	
	Range & Resolution	Accuracy	Range & Resolution	Accuracy	Range & Resolution	Accuracy
AC Voltage	200.0/600 V	1.2%	200.0/600 V	1.2%	2000m/200.0/600 V	1.2%
DC Voltage	200.0m/2000m/200.0/600 V	0.5%	20.00/200.0/600 V	0.5%	2000m/200.0/600 V	0.5%
AC Current	200.0 A	3.0%	200.0 A	3.0%	200.0 A	3.0%
Resistance	200.0/200.0k Ω	1.0%	200.0/200.0k Ω	1.0%	200.0/200.0k Ω	1.0%
Capacitance	—	—	200.0 μ F	3.0%	200.0 μ F	3.0%
Frequency	2.000k/20.00k/40.00k Hz (Auto)	0.1%	2.000k/20.00k/40.00k Hz (Auto)	0.1%	—	—

