2000 Amp Clamp Meters

- 2000A current capability
- Broad frequency response – 40Hz to 1kHz
- Low battery indicator
- Overload protection on all ranges
- Lifetime limited warranty
  Includes carrying case

Description	Cat. No.
2000AAC Clamp Meter, data hold	**61-740**
2000AAC Clamp Meter, DC current, output terminal, diode test, max hold	**61-741**
2000AAC Clamp Meter, True RMS, DC current, output terminal, diode test, peak hold	**61-742**

Specifications	61-740		61-741		61-742	
	Range & Resolution	Accuracy	Range & Resolution	Accuracy	Range & Resolution	Accuracy
AC Voltage	40.00/400.0/750 V	1.0%	400.0/750 V	1.5%	40.00/400.0/750 V	1.5%
DC Voltage	40.00/400.0/750 V	1.0%	400.0/1000 V	1.0%	40.0/400.0/1000 V	1.0%
AC Current	400.0/2000 A	1.0%	400.0/2000 A	1.5%	400.0/1700/2000 A	1.5%
DC Current	—	—	400.0/2000 A	1.5%	400.0/2000 A	1.5%
Resistance	400.0/4.000k/40.00k/400k Ω	1.5%	400.0/4000 Ω	1.5%	400.0/4000 Ω	1.5%
Frequency	—	—	—	—	4000 Hz	1.5%
Diode Test	—	—	✔	—	✔	—
Analog Output	✔	—	✔	—	✔	—

CE