800 Series Power Clamps

- 2000A AC/DC current capability
- True RMS
- Kilowatts
- Data hold
- Auto ranging
- DC current zero function
- Overload protection
- Lifetime limited warranty
- CAT III – 600V
  Includes carrying case

Description	Cat. No.
Power Clamp, 2000AAC current capability, 2500ADC current capability, temperature, analog output (current ranges), relative mode, min/max, audible continuity	**61-800**
Power Clamp, 2000A AC/DC current capability, 3-phase, kVA, kVAR, power factor, frequency, dual display, memory recall	**61-802**

Specifications	61-800		61-802	
	Range & Resolution	Accuracy	Range & Resolution	Accuracy
AC Voltage	4.000/40.00/400.0/600 V	1.5%	200.0/500/600 V	1.5%
DC Voltage	400.0m/4.000/40.00/400.0/600 V	1.5%	200.0/500/800 V	1.5%
AC Current	400.0/1000/2100 A	1.5%	200.0/500/2000 A	1.5%
DC Current	400.0/2000/2500 A	1.5%	200.0/500/2000 A	1.5%
Kilowatt (True Power)	40.00/400.0/1200 kW	2.5%	100.0/1000/1200 kW	2.0%
kVAR (Reactive Power)	—	—	100.0/1000/1200 kVAR	2.0%
kVA (ApparEnt Power)	—	—	100.0/1000/1200 kVA	2.0%
Resistance	40.0/400.0 Ω	1.0%	—	—
Frequency	—	—	50.0/60.0/400.0 Hz	0.5%
Temperature	-50.0° to 1000° F	1.0%	—	—