To Order

To form a Catalog Number

F 1 1 0 - _ _ _ - S - 0 2 - _ - _ _

1 2 3 4 5 6 7 8

1 Source

F = Linear fluorescent

2 Style

110 = Small enclosed **TAC**, **integral** ballast

3 Lamp

_ _ _ = **Lamp Code**

Lamp Wattage (see chart below)

Reflector Configuration, specify **1**, **3** or **5** (see chart below)

A = T8 Fluorescent
T = T5 Fluorescent

Example: **A532** = three nominal 4' reflectors, each for use with one 32W T8 lamp, one 3-lamp ballast in center housing

Reflector Configuration

1	1 Lamp Ballast 1 Housing
3	2 Lamp Ballast 2 Housings (Master/Satellite)
5*	3 Lamp Ballast 3 Housings (Satellite/Master/Satellite)

* Configuration 5 not available for dimming, or for T5 lamps

Lamp Wattage

Lamp Length (nominal)	*Lamp Wattage (Lamp Number)*		
	T8	*T5*	*T5 HO* *
2'	**17** (F17T8)	**14** (F14T5)	**24** (F24T5/HO)
3'	**25** (F25T8)	**21** (F21T5)	**39** (F39T5/HO)
4'	**32** (F32T8)	**28** (F28T5)	**55** (F55T5/HO)
5'	**40** (F40T8)	**35** (F35T5)	**80** (F80T5/HO)

For complete lamp and ballast information, see Accessories Section
Standard T5 lamp color is 3000K / 80+ CRI. T8 lamps by others
* Consult sales representative for availability of T5 HO

W 5.1

Project: _____

4 Mounting

S = Ceiling mount
Note: For cantilever or pendant mounting, see Accessories Section

5 Finish

02 = Semi-gloss white

6 Voltage/Ballast

Electronic	*Dimming***
1 = 120V	T = 120V
2 = 277V	V = 277V
3 = 347V (Canada)*	

* Consult sales representative for availability of 347V for 2' and 3' T5, and all T5 HO
** Dimming not available for Configuration **5** (3-lamp ballast)
Consult sales representative for dimming with T5 lamps

7 Option (See Accessories Section for specifications)

00 = No options
0B = Snap-in parabolic cross baffle, specular aluminum, provides 35° lengthwise shielding
0E = Integral emergency battery pack
XX = For modification not listed, include detailed description. Consult factory prior to specification

8 Standard

0 = UL, Underwriters Laboratories
J = CSA, Canadian Standards Association

Example

F110 - A532 - S - 02 - 1 - 000

Small enclosed **TAC** for use with three 4' T8 lamps. Three housings, each 49" long, join for an overall length of 12'-3" (not including decorative end plates). Integral 120V electronic 3 lamp ballast (center housing is master). Semi-gloss white. UL. Order decorative end plates separately.

Type: _____

Accessories

Order separately. See Accessories Section for specifications.

ATDE0020 = **Decorative end plates**, pair, semi-gloss white

VL _ **0218** _ = **Cantilever**, 18" (460mm) setback, semi-gloss white, recommended for displays up to 8' (2.4m) high

0 = UL
J = CSA

L = Electrical feed
M = Non-electrical feed

VL _ **02** _ _ = **Pendant**, semi-gloss white

0 = UL
J = CSA

Length in inches, up to 60" (1.5m), 6" minimum

N = Electrical feed
P = Non-electrical feed

AFK000X _ = Ballast **fuse** kit

0 = UL
J = CSA

elliptipar

elliptipar
114 Orange Avenue, West Haven, Connecticut 06516, USA
Voice 203.931.4455 • Fax 203.931.4464

The external shapes of the asymmetric reflectors are trademarks of **elliptipar**
Certain products illustrated may be covered by applicable patents and patents pending. For a list of patents, see Contents pages. These specifications supersede all prior