


**belden.com** The Belden Catalog Cable College Corporate Information Sales and Service DISTRIBUTOR DESK Copyright © 2002 Belden Inc.

Cable finder Technical Info Conduit Capacity Chart Connector Cross Ref. Distributor Login Help Customer Service Distributor Locator

Back New Search

Search

**FULL TECHNICAL SPECS**



**1075A Composite - Power Limited Tray Cable 300 Volts**

<b>Total # Cond.</b>		<b># Pairs</b>			
5		2			
<b>AWG</b>	<b>Stranding</b>	<b>Type</b>	<b>Insulation</b>	<b>Insulation Thickness (in.)</b>	<b>Shield</b>
20	(7x28)	BC - Bare Copper	PVC - Polyvinyl Chloride	.01400	Individual/Overall Aluminum Foil-Polyester Tape
<b>Jacket</b>	<b>Jacket Thickness (in.)</b>	<b>Nom. Core OD (in.)</b>	<b>Nom. OD (in.)</b>	<b>Nom. Cond. DCR (Ohms/M')</b>	<b>Nom. Cap. (pF/ft)</b>
PVC - Polyvinyl Chloride	.0420	.2530	.3370	9.500	30.000

For technical data, click the button below <input type="button" value="Tech Data"/> or call 1-888-Belden8	For available colors, click the button below <input type="button" value="Put-ups &amp; Colors"/> or call 1-888-Belden8
---	--

**Description**

Multi-Conductor, Composite, 2 pairs (20 AWG, stranded (7x28) BC - Bare Copper conductors) plus 1 communication wire (22 AWG, stranded (7x30) BC - Bare Copper conductors), PVC - Polyvinyl Chloride insulation, Individual Aluminum Foil-Polyester Tape (Beldfoil) shield with 22 AWG stranded (7x30) tinned copper drain wire, Overall Aluminum Foil-Polyester Tape (Beldfoil) shield with 20 AWG stranded (7x28) tinned copper drain wire, 100% shield coverage, sunlight resistant PVC - Polyvinyl Chloride jacket with nylon ripcord. Applicable Specifications: UL PLTC or ITC or CMG or C(UL) CMG, FT4, IEEE 1202. Flame Resistance: UL 1581 Vertical Tray CSA FT4 Flame Test. Industrial Automation & Process Control Cables. Power Limited Tray Cable. Other insulation and jacket options are available. These cables are suitable for installation in wet or dry locations. Cable jackets are sunlight resistant, impervious to moisture and vapor penetration, and non-propagating. Alternate conductor color coding is available as a special order. Multiple pair cables have each pair numbered for ease of identification. Individually shielded and overall shielded - individually shielded pairs with an overall shield are recommended for use in instrument and control applications where optimum noise rejection is required. Individual pair shields are fully isolated from each other and contain a separate drain wire for grounding, to provide maximum protection from crosstalk and common mode interference. Cables with an overall shield provide additional electrostatic noise protection. BELDFOIL is a Belden registered trademark.

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors or omissions may occur. This listing of information is presented as a courtesy and does not ensure that a product with these specifications is available. Specification and availability should be confirmed with a call to our sales representative or to Customer Service. Have a question? Call us at 1-800-BELDEN-1 or send us a [comment](#)

07/30/02

# TECHNICAL DATA

Customer Number • 000001

Customer Name •

To display Technical Data, enter a Product Code and press Go.

<b>Product Code</b>	<input type="text" value="1075A"/>	<b>Go</b>
	<b>Example: 9269</b>	
<b>Product Search</b>		

11-21-00 REV.7

1075A

I. DESCRIPTION:

-----  
 POWER LIMITED TRAY CABLE - 2 PAIRS + COMMUNICATION WIRE  
 PAIRS ARE 20 AWG (7X28) BARE COPPER, PVC INSULATION,  
 INDIVIDUALLY BELDFOIL SHIELDED W/ 22 AWG (7X30) TINNED  
 COPPER DRAIN WIRE, COMMUNICATION WIRE IS 22 AWG  
 (7X30) BARE COPPER, PVC INSULATION, OVERALL BELDFOIL  
 SHIELD W/ 20 AWG (7X28) TINNED COPPER DRAIN  
 WIRE, PVC JACKET WITH NYLON RIPCORD.

II. ELECTRICAL CHARACTERISTICS:

-----  
 MAX. OPERATING VOLTAGE: 300 V RMS  
 NOM. CONDUCTOR DC RESISTANCE  
 @ 20 DEG. C (20/22 AWG): 9.5/15 OHMS/1000 FT  
 NOM. SHIELD DC RESISTANCE  
 @ 20 DEG. C:  
 (INDIVIDUAL): 51 OHMS/1000 FT.  
 (OVERALL): 30 OHMS/1000 FT.  
 NOM CAPACITANCE BETWEEN  
 CONDUCTORS AT 1KHZ: 30 PF/FT.  
 CONDUCTOR AND SHIELD @ 1KHZ: 55 PF/FT.  
 MAX. CONTINUOUS CURRENT PER  
 CONDUCTOR @ 25 DEG. C: 4.8 A  
 NOM LOOP INDUCTANCE: .19 MICROHENRIES/FT.

III. PHYSICAL CHARACTERISTICS:

-----  
 TEMPERATURE RATING: -30 TO +105 DEG. C  
 INSULATION MATERIAL & DIA: PVC; .068"  
 JACKET MATERIAL (COLOR): PVC (BLACK) SUN RES  
 TYPE SHIELDS AND % COVERAGE: MYLAR/AL FOIL; 100%  
 MAX. PULLING TENSION: 97.3 LBS ESTIMATED  
 NOM. WEIGHT/1000 FT.: 68.1 LBS ESTIMATED  
 MIN. BEND RADIUS: 3.5"  
 JACKET DIAMETER: .337" NOMINAL  
 APPLICABLE SPECIFICATIONS: UL PLTC OR ITC OR CMG

	OR C(UL) CMG, FT4,
	IEEE 1202
FLAME RESISTANCE:	UL 1581 VERTICAL TRAY
	CSA FT4 FLAME TEST
	FLAME TEST
COLOR CODE:	BLACK & WHITE NUMBERED
	PAIRS, ORANGE COM WIRE