

Products: Main : C: Instrumentation and Thermocouple Cable : Instrumentation - 600 Volt Type TC...Single & Multiple Triads I/S & O/S...LS-ZH :

Specification

HW121

Instrumentation Cable

600 Volt Type TC, 90°C
 Single & Multiple Triads
 Individual and Overall Shield
 XLP Insulation
 Low Smoke Zero Halogen Jacket
 Tinned Copper Conductors

Catalog Number	Size AWG	Number of Triads	Insulation Thickness	Jacket Thickness	Overall Diameter Inch	Net Weight Lbs/Mft
HW121 01602	16	2	32	60	0.64	170
HW121 01604	16	4	32	60	0.74	268
HW121 01606	16	6	32	60	0.93	422
HW121 1601T	16	1	32	60	0.35	67

Application:

LifeGuard™ Low Smoke Zero Halogen* cable is for use in instrumentation and process control applications where protection from electrostatic interference is required. It is highly flame-retardant, produces very small amounts of smoke when burned and contains no halogens. LifeGuard™ cable is ideal for applications where a high degree of equipment and personnel protection is required.

LifeGuard™ cable is NEC listed as Type TC and approved for installation indoors or outdoors, aerially, in conduits, ducts, cable trays and direct burial in circuits not exceeding 600 volts. It may be installed in temperatures as low as -30°C and used in NEC Class 1, Division 2 hazardous locations. It is NEC approved for continuous operation at 90°C in wet and dry locations, 130°C for emergency overload conditions, and 250°C for short circuit conditions.

Product Features:

- Tray rated
- Sunlight-resistant
- Approved for direct burial
- Tinned conductors provide ease of termination and added protection in caustic environments
- Superior electrostatic interference protection from individual and overall shield
- Very low smoke production when burned
- Produces zero halogens during fire – less toxic and corrosive
- Environmentally safe – lead, sulfur and halogen free
- Highly chemical resistant
- Very flame retardant
- Burns to an ash – does not exhibit thermoplastic drip
- Excellent compression and impact resistance
- Superior tensile strength and abrasion resistance
- Flexible jacket with low coefficient of friction

Conductors:

7 strand tin coated, soft annealed copper per ASTM B-33, Class B stranding per ASTM B-8.

Insulation:

Cross-linked polyethylene (XLP)per UL Standard 44

Individual Shield:

Aluminum-polymer tape providing 100% coverage with a flexible 7 strand tinned copper drain wire.

Overall Shield:

Aluminum-polymer tape providing 100% coverage with a flexible 7 strand tinned copper drain wire.

Jacket:

Sunlight-resistant and flame-retardant, Low Smoke Zero Halogen polyolefin per UL Standard 1277. A ripcord is applied longitudinally under the jacket to facilitate stripping.

Flame Tests:

UL Standard 1581 70,000 BTU/hr flame test

Color Code:

ICEA Method 1: black, white and red twisted triads with numbers

Additional Standards:

- UL Standard 1685
- NEC Type TC per articles 336, 392, and 501.4 (b) and Class 1 circuits per NEC article 725

*Some cable insulations may contain trace amounts of halogens.



1-800-HOU-WIRE
2002 Product Catalog